



Fire Nozzles

Part Number: 19mm inlet, DE01-500-19
25mm inlet, DE01-500-25

Hose Reel Fire Nozzle

Automatic pressure control, stainless steel slide valve, effortless on/off control, low maintenance, rapid pulsing facility. Available with 19mm or 25mm inlet. Wide flow range from 40 L/Min to 500 L/Min



Part Number: 500 model, DE02-500-25
750 model, DE02750-25



Mainline Fire Nozzle, available in select flow and constant flow models. Stainless steel spinning teeth, long range penetrating jet, dense wide angle fog pattern.

Select flow model 125, 250, 375 & 500 L/Min or
285, 460, 600 & 750 L/Min

Constant flow models can be fixed at any of the above flow rates.

Part Number: 500 model, DE01-500-25
600 model, DE01-600-25



Mainline Fire Nozzle, Automatic Valve.

Automatic pressure control, stainless steel slide valve, effortless on/off control, low maintenance, rapid pulsing facility. Available with 2.5" instantaneous as standard, however all international inlets are available. Wide flow range from 50 L/Min to 500 L/Min



AWG style nozzle, available in light alloy or gunmetal.



Unifire nozzle, available with light alloy inlets or gunmetal



Diffuser nozzle, available in light alloy or gunmetal.

FlameSkill Ltd
1 Morton Peto Estate
Great Yarmouth
Norfolk
NR31 0LT
Tel: 01493 440464
Email: admin@flameskill.co.uk
Web: www.flameskill.co.uk