



## Powder Fire Extinguishers


### Powder Fire Extinguishers

- Using leading technology in manufacture all cylinders are drawn cans
- High quality plated brass body valve
- 1kg and 2kgs extinguishers with fixed nozzle and wire bracket
- 3kgs extinguisher with wire bracket and quick release strap to meet transport requirements
- 4kgs and higher are supplied with flexible hose, nozzle and durable plastic skirt
- Clear screen printed operating instructions for visibility and legibility

Supplied factory filled and pressurised



Model Ref	FS06-015-000	FS06-025-000	FS06-035-000	FS06-045-000	FS06-065-000	FS06-096-000
Capacity	1kg	2kg	3kg	4kg	6kg	9kg
Fire rating	5A 34B	13A 70B	13A 89B	21A 113B	27A 183B	34A 183B
Operating pressure	14 bar at 20°C	14 bar at 20°C	14 bar at 20°C	14 bar at 20°C	14 bar at 20°C	14 bar at 20°C
Operating temperature	-30°C to +60°C	-30°C to +60°C	-30°C to +60°C	-30°C to +60°C	-30°C to +60°C	-30°C to +60°C
Height	335mm	400mm	440mm	485mm	530mm	610mm
Diameter	85mm	110mm	130mm	140mm	162mm	182mm
Filled weight (approx)	2kg	3.6kg	5kg	6.9kg	10kg	14kg



FlameSkill Ltd  
 1 Morton Peto Estate  
 Great Yarmouth  
 Norfolk  
 NR31 0LT  
 Tel: 01493 440464  
 Email: [admin@flameskill.co.uk](mailto:admin@flameskill.co.uk)  
 Web: [www.flameskill.co.uk](http://www.flameskill.co.uk)